Material Safety Data Sheet



1. Identification of the material and supplier

<u>Names</u>		
Product name	:	Sikadur 31/41 Rapid Part B
ADG	:	Corrosive solid, n.o.s.
<u>Supplier</u>		
Supplier/Manufacturer	:	Sika Australia Pty. Ltd. 55 Elizabeth Street (Locked Bag 482 BDC) Wetherill Park, NSW 2164 Australia
Telephone no.	:	+61 2 9725 11 45
Fax no.	:	+61 2 9725 33 30
Emergency telephone number	:	+61 1800 033 111
Use of the substance/mixture		Chemical product for construction and industry

2. Hazards identification

Classification	: C; R34 R43 R52/53
Risk phrases	 R34- Causes burns. R43- May cause sensitisation by skin contact. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	 S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39- Wear suitable protective clothing, gloves and eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Statement of hazardous/dangerous nature	: HAZARDOUS SUBSTANCE. DANGEROUS GOODS.

3. Composition/information on ingredients

Mixture	: Yes.			
0.0.4/ 0.4.4) 1.1		05540.04.0	40	-

2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine

25513-64-8

10 - <30

Other ingredients, determined not to be hazardous according to Safe Work Australia criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First-aid measures

First-aid measures

: Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Sikadur 31/41 Rapid Part B

4. First-aid measures

	50165
Ingestion	: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Extinguishing media	
Suitable	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Not suitable	: Do not use water jet.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazchem code	: 2X

6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Version :	1	Page: 2/7

6. Accidental release measures

Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from acids. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits	:	No exposure standard allocated.
Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Exposure controls		
Engineering measures	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Version :	1	Page: 3/7

Sikadur 31/41 Rapid Part B

8. Exposure controls/personal protection Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid. [Liquid.]
Colour	: Black.
Odour	: Amine-like.
Boiling point	: >200°C (>392°F)
Vapour pressure	: 0.03 kPa (0.225 mm Hg) [20°C]
Density	: 1.7 g/cm ³ [20°C (68°F)]
Flash point	: Closed cup: 89°C (192.2°F)
рН	: 11 [Conc. (% w/w): 50%]

10. Stability and reactivity

Stability	1	The product is stable.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Materials to avoid	:	Reactive or incompatible with the following materials: acids oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Potential acute health effects

Inhalation	:	May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.				
Ingestion	1	May cause burns to mouth, throat and stomach.				
Skin contact	1	Corrosive to the skin. Causes burns. May cause sensitisation by skin contact.				
Eye contact	:	Corrosive to eyes. Causes burns.				
Acute toxicity						
Product/ingredient name 2,2,4(or 2,4,4)-trimethylhexar diamine	ıe-		<mark>esult</mark> D50 Oral	Species Rat	Dose 910 mg/kg	Exposure -
Conclusion/Summary	:	Not available				
Potential chronic health effec	<u>ts</u>					
Chronic toxicity						
Conclusion/Summary	1	Not available				
Carcinogenicity						
Conclusion/Summary	1	Not available				
<u>Mutagenicity</u>						

Version : 1	Page: 4/7
-------------	-----------

11. Toxicological information

Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Chronic effects	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>toms</u>
Inhalation	: No specific data.
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eyes	: Adverse symptoms may include the following: pain watering redness
Target organs	: Contains material which may cause damage to the following organs: kidneys, lungs, upper respiratory tract, skin, eye, lens or cornea, testes.

12. Ecological information

Environmental effects	: Harmful to aquatic orga environment.	anisms, may cause long-	term adverse e	effects in the aquatic
Aquatic ecotoxicity				
Product/ingredient name	Test	Result	Species	Exposure
2,2,4(or 2,4,4)-trimethylhexand diamine	ne-1,6	Acute EC50 29.5 mg/l	Algae	72 hours
Conclusion/Summary	: Not available.			
Other ecological information				
Biodegradability				
Conclusion/Summary	: Not available.			
Other adverse effects	: No known significant ef	fects or critical hazards.		

13. Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

ADG		
UN number	:	UN1759
ADG Class	:	8
Packing group	:	III
Proper shipping name	:	Corrosive solid, n.o.s.
Contains	:	Trimethylhexamethylenediamines
Label No.	:	8
Hazchem code	:	2X
ADR		
UN number		UN1759
ADR Class	:	8
Classification code	:	C10
Packing group	-	III
Proper shipping name		Corrosive solid, n.o.s.
Contains		Trimethylhexamethylenediamines
Label No.	:	8
<u>IMDG</u>		
UN number	:	UN1759
IMDG Class	÷	8
Packing group	÷	а Ш
Proper shipping name	•	Corrosive solid, n.o.s.
Contains		Trimethylhexamethylenediamines
Emergency schedules		F-A, S-B
(EmS)	•	, , , , , , , , , , , , , , , , , , ,
Marine pollutant	:	No.
Label no.	:	8
ΙΑΤΑ		
UN number		UN1759
IATA Class	÷	8
Packing group		
Proper shipping name	•	Corrosive solid, n.o.s.
Contains		Trimethylhexamethylenediamines
Label no.	:	8
	•	0

15. Regulatory information

Standard for the Uniform Sch	neduling of Drugs and Poisons	
6		
Control of Scheduled Carcine	ogenic Substances	
Ingredient name No listed substance		<u>Schedule</u>
Australia inventory (AICS)	: Not determined.	
EU Classification	: C; R34 R43 R52/53	

16. Other information

Person who prepared the : Validated by DeSilva on 09.10.2012. MSDS

Date of previous issue : No previous validation.

✓ Indicates information that has changed from previously issued version.

Disclaimer

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.